

DK-22 Knee Pad

An advanced knee pad that combines a PVC outer shell with gel-enhanced inner padding to provide both comfort and protection. It helps reduce pressure during prolonged kneeling tasks, delivering a more comfortable and stable working experience.



PVC Outer Shell

Protects the knees against impact and abrasion on hard surfaces such as concrete, stone, and metal. Helps distribute concentrated pressure to protect the kneecap.

Single Strap Retention System

The adjustable strap provides a secure and stable fit during use.



Technical Specifications

Outer Shell Material	PVC
Inner Padding Material	EVA & Gel Foam
Carrier Textile Body	600D Polyester
Dimensions	24 x 17.5 cm
Size	Standard (Compatible with adjustable strap system)
Carton / Packaging	12 / 1 Pair
Performance	Type 1 - Level 1
Standards	EN 14404-1:2024 EN 14404-2:2024



STARLINE

Standards

The **EN 14404:2024** series specifies test methods, performance requirements, and classification criteria for industrial knee protectors intended for kneeling work. This standard has been developed to provide protection against mechanical hazards associated with prolonged knee contact.

EN 14404-1:2024 – Specifies the test methods for knee protectors, including penetration resistance, force distribution, and ergonomic requirements.

EN 14404-2:2024 – Specifies the performance and design requirements for wearable knee protectors attached to the leg (Type 1).

This product is classified as Category II Personal Protective Equipment under PPE Regulation (EU) 2016/425.

EN 14404:2024 classifies knee protectors according to penetration resistance and test surface conditions. Tests are carried out on both flat and uneven surfaces. Higher performance levels provide increased resistance to penetration.

This standard specifies the requirements and performance levels for wearable knee protectors (Type 1) intended to reduce knee injuries caused by continuous pressure and penetration during kneeling work. It also specifies marking requirements and the information to be provided by the manufacturer. Where protection against additional hazards is required, the relevant requirements of other applicable standards shall apply.

HOW TO SELECT PROTECTION PERFORMANCE LEVELS

Level 0: Provides protection on flat and uneven surfaces but does not provide penetration resistance.

Level 1: Provides protection on flat and uneven surfaces with penetration resistance of (100 ± 5) N.

Level 2: Provides protection on flat and uneven surfaces with penetration resistance of (250 ± 10) N.

Areas of Use



Construction and
Building



Flooring Applications



Mechanical
Maintenance



Assembly Operations

Designed for applications requiring prolonged kneeling. Suitable for use in construction and jobsite activities, ceramic and tile installation, parquet and flooring applications, plumbing and maintenance work, automotive and mechanical service operations, as well as gardening and landscaping.

STARLINE

Instructions for Use



Care and Cleaning

The product should be inspected before each use. Contamination, damage, or improper use may adversely affect its protective performance. The knee pad is not water-resistant. Clean the product by wiping it with a clean cloth. Do not dry the product near heat sources. If any damage is detected, the product should not be used and must be replaced.



Service Life


The knee pad has a minimum service life of 2 years; however, this period may vary depending on the conditions of use. Environmental factors such as extreme temperatures, chemicals, sunlight, and improper storage may affect the product's performance and service life. The product should be inspected before each use.



Storage

When not in use, the product should be stored in a dry and well-ventilated area away from extreme temperatures. Changes in environmental conditions, especially temperature and humidity, may reduce its protective performance. Do not place heavy objects on the product. Excessive folding should be avoided whenever possible, and the product should preferably be stored in an upright position. If the product is wet, allow it to dry completely before storage.

Order Information

MODEL	Size	Barcode	Carton Quantity	Carton Dimensions	 Carton Weight
DK-22	Standard	8680907012102	12 Pairs	59x51x26.5 cm	8.00 kg