

### E-041-YS Leather Glove

Hand palm and all fingers parts are manufactured from fine split leather. Upper side of the hand is composed of cotton stripe fabric. Reinforcement is available on the palm, thumb and index finger that provides better resistance to tear and puncture. There is a sweat absorbing cotton lining that reduces heat conduction in the palm. Comfortable to wear and remove through its safety cuff.

#### Upper Material

Cotton fabric that allows hand to breathe.

#### Reinforcement Material

In order to increase the strength of the glove, split leather is reinforced on the palm, thumb and index finger.

#### Marking Field

Include all information required to be provided as per the European norms.

#### Safety Cuff

Has a model which allows glove to be easily removed. Protects wrist area. Has a length of 7 cm.




### Technical Specifications

Glove Palm Material*	Split Leather
Glove Back Material	Green striped cotton fabric
Lining Material	Cotton
Sizes	10/XL
Carton Content	120 Pairs
Packaging	1 Pair
Category	CAT II
Standards	EN 388:2016+A1:2018 (2122X) EN ISO 21420:2020

\* Starline products do not contain pig leather.

# STARLINE

## ● REINFORCEMENT AREA AND LINING INFORMATION



 Reinforced Area

### REINFORCEMENT AREA

E-041-YS Gloves are sewn in one piece. Additional leather reinforcement is available on the palm, thumb and index finger that provides better protection.



### COTTON LINING

Ensures hand to work comfortably through cotton lining. Allows skin to breathe with the breathable texture against sweats.

## ● STANDARDS

These gloves are intended to protect the hands against mechanical hazards as defined in the PPE Regulation (EU) 2016/425. This product is certified as per EN ISO 21420 (General requirements and inspection methods for protective gloves) and EN 388 (Mechanical Risk Protection).

EN 388:2016 +A1:2018 EN ISO 21420: 2020



**2122X**

## ● Areas of Use



Construction and Building



Automotive and Transportation



Mine



Cleaning



Logistic and Storage




Wood

Suitable for use in the wood, production of wood products and cork products, building and outdoor construction works, transportation and storage works, mining and quarry, rough cleaning works.

## STANDARD REMARKS

### EN 388:2016 +A1:2018 EN 388 Protective Gloves Against Mechanical Risks



abc def

This standard covers features and test methods of the protective gloves against mechanical risks such as abrasion, blade cut, tear and puncture.

#### REQUIREMENTS:

Protective gloves complying with this standard should fulfill all applicable requirements of EN ISO 21420. Performance level of a protective glove against mechanical risks should exceed the lowest level for each one in the following table (abrasion, blade cut, tear and puncture).

Note– Gloves fulfilling the requirements for puncture resistance may not be suitable for sharp-pointed objects such as hypodermic needles.

PERFORMANCE LEVELS	1	2	3	4	5
A - Abrasion resistance (cycles)	100	500	2000	8000	-
B - Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0
C - Tear resistance (N)	10	25	50	75	-
D - Puncture resistance (N)	20	60	100	150	-

### EN ISO 21420 :2020



#### EN ISO 21420 General Specifications and Test Methods

This standard specifies the general requirements for the glove design and construction, protection against hazards, comfort, efficiency and marking and information applicable to all protective gloves. This standard also applies to arm protections.

Many gloves designed for electrical technicians or the most private applications such as surgical operations are governed by private and strict standards.

GLOVE SIZE	Fits Hand Size	Hand Circumference / Length	Minimum Glove Length
6	6	152/160 mm	220 mm
7	7	178/171 mm	230 mm
8	8	203/182 mm	240 mm
9	9	229/192 mm	250 mm
10	10	254/204 mm	260 mm
11	11	279/215 mm	270 mm

# STARLINE



## Maintenance and Cleaning

We recommend you to clean gloves by a brush made of synthetic materials. Glove cleaning should not be carried out through rigid and tearing materials. It should be never washed by hand or in the washing machine. It is the responsibility of user to control whether glove is suitable for intended use or not, whether it is complete or not and whether protective functions are undamaged or not. User should carry out an examination against potential defects which are likely to adversely affect protection functions (punctures, tears, damaged seams, etc.).



## Service Life

Gloves should be used within five years as of the manufacture date. Service life of the gloves is affected by several factors such as cold, hot, chemicals, sunlight and inadvisable storage.



## Storage

Storage is a part of the maintenance and cleaning but is often ignored. Protective gloves should be stored in their original packaging which will keep them away from direct sunlight, chemicals and abrasive materials and protect them against physical damages of the hard surfaces or materials when it is not used or during shipment. Product should be stored in a dry and well-ventilated place. Availability of excessive humidity or intense light may adversely affect the product quality.

## ● Order Information

MODEL	Size	Barcode	Box Quantity	Box Dimension	Box Weight
E-041-YS	10 / XL	8680907005364	120 Pairs	51 x 31 x 51cm	20kg.