

E-540 Natural Rubber Gloves

This product is designed to protect the user against high-grade hazards in accordance with the standards met. All parts up to the wrist have a sandy structure on the palm and hand. In this way, it provides high grip and non-slip on wet and moist surfaces. It protects against sweating thanks to its cotton lined inner structure and has a heat resistant structure. Tested against 250 ° C heat conduction. In addition to its suitability for food, it provides comfortable use in food production facilities or hot services.



Marking Field

It contains all the information that should be given according to European norms.

Upper Material

It is made of natural rubber material for working in the environments required by dry and wet clutches.

Glove Lining


Thanks to its fabric fiber lining structure, it can be easily worn and removed and allows comfortable use.

Technical Specifications

Lining Material	Fabric Lining
Sizes	6.5, 7.5, 8.5, 9.5, 10.5
Color	Blue
Length / Thickness	300mm / 0.75mm
Box Amount	144 Pairs
Packaging	1 Pair
Category	CAT III
Standards	EN 388:2016+A1:2018 (4131X) EN 374-5:2016 EN ISO 374-1:2016+A1:2018/Type A EN 407:2020 (X1XXXX) EN ISO 21420:2020

STARLINE

● GLOVE TEXTURE and LINING MATERIAL



SANDY TEXTURE

Thanks to the sandy texture applied on the palm of the glove, it provides the anti-slip properties on wet and dry surfaces. Thanks to the texture, objects can be gripped more firmly.



COTON LINING

Thanks to the cotton lining, it can be easily worn and removed and allows comfortable use. Minimizes hand sweats.

● STANDARDS

These gloves are designed to protect hands against irreversible or fatal risks as defined in the PPE Regulation (EU) 2016/425. This product has been tested according to the following standards, EN ISO 21420:2020 (General requirements and test methods for protective gloves), EN 388:2016+A1:2018 (Protective gloves against mechanical risks), EN 374-1:2016+A1:2018 (Protection against chemicals and micro-organisms), EN 407:2020 (Protection against thermal risks).

EN 388:2016
+A1:2018



4131X

EN ISO 21420
:2020



EN ISO 374-1:
2016+A1:2018/Type A



AKLMNPST

EN ISO 374-5
:2016



EN 407
:2020



X1XXXX




● Areas of Use



It is suitable for use in the manufacture of food products. It can also be used in pharmaceutical industry and laboratory jobs, jobs requiring resistance to chemicals. It is a very suitable glove especially for people who are engaged in cement works in the construction industry. It can be used in the cleaning industry where there are risky chemicals.

STANDARD REMARKS

EN 388:2016



a b c d e f

EN 388:2016 Protective Gloves for Mechanical Risks

This standard covers features and test methods for protective gloves against mechanical risks such as abrasion, cutting, tearing, puncturing.

FEATURES:

Protective gloves conforming to this standard must meet all applicable properties of EN ISO 21420. The performance level of a protective glove against mechanical risks should be at a higher level for one of the attributes (wear, knife cutting, tearing, puncture and impact protection) that are classified according to the least features of each level shown in the table below.

Note - Gloves that meet the specifications for puncture resistance may not be suitable for protection against sharp-pointed objects such as hypodermic needles.

The letter **X** means that the test has not been done or can not be performed.

PERFORMANCE LEVELS	1	2	3	4	5
a - Abrasion resistance (number of cycles)	100	500	2000	8000	-
b - Cut resistance (index)	1,2	2,5	5,0	10,0	20,0
c - Tear resistance (N)	10	25	50	75	-
d - Puncture resistance (N)	20	60	100	150	-

PERFORMANCE LEVELS	A	B	C	D	E	F
e - Cut Resistance (N)	2	5	10	15	22	30
f - Protection Against Impact	Pass (P) / Failed (No sign)					

EN ISO 21420: 2020 EN ISO 21420:2020 General Specifications and Test Methods

2020



This standard specifies the general requirements for the glove design and construction, protection against hazards, comfort, efficiency and marking and information applicable to all protective gloves. This standard also applies to arm protections.

Many gloves designed for electrical technicians or the most private applications such as surgical operations are governed by private and strict standards.

GLOVE SIZE	Fits Hand Size	Hand Circumference / Length	Minimum Glove Length
6	6	152/160 mm	220 mm
7	7	178/171 mm	230 mm
8	8	203/182 mm	240 mm
9	9	229/192 mm	250 mm
10	10	254/204 mm	260 mm
11	11	279/215 mm	270 mm

* For more detailed information on Standards, you can obtain **EN European Glove Standards Guidelines** from www.starlinesafety.com.

STANDARD REMARKS

EN 374-1/Type A EN 374-1/Type B EN 374-1/Type C



UVWXYZ



XYZ



Marking of Protective Gloves from Chemicals

Type A and Type B gloves must be accompanied by coding letters under the “chemical resistant” pictogram shown on the side.

Gloves marked with Type C do not use the coding letter.

These coding letters refer to the list of chemicals

defined in the standard. The minimum permeability time for type C gloves is 10 minutes for a chemical in the list. For Type B, 30 minutes for at least 3 chemicals and 30 minutes for Type A for at least 6 chemicals.

EN 374-4: 2013 New Distortion Test

After exposure to a chemical substance for a while, a new decay test was performed to measure the change in the physical properties of the glove. Fragmentation can be seen as swelling, flaking, discoloration, relaxation, hardening, softening or dimensional change. Tests according to EN 374-4: 2013 must be carried out for each requested chemical.

- Distortion test (deterioration of the physical properties of the gloves in contact with the chemical) according to EN 374-4: 2013.

- In order to be protective against chemicals in the list, it should be subjected to Penetration and Distortion tests.

- Distortion test results should be in the information brochure.

LIST OF CHEMICAL SUBSTANCES USED IN EXPERIMENT:

CODE	CHEMICAL MATTER	CAS NUMBER	CLASS
A	Methanol	67-56-1	Primary Alcohol
B	Nail polish remover	67-64-1	ketones
C	Acetonitrile	75-05-8	Nitrile Compound
D	Dichloromethane	75-09-2	Chlorinated Paraffin
E	Carbon Disulfide	75-15-0	Organic Compound Containing Sulfur
F	Toluene	108-88-3	Aromatic Hydrocarbon
G	Diethylamine	109-89-7	Amine
H	Tetrahydrofuran	109-99-9	Heterocyclic And Ester Compound
I	Ethyl Acetate	141-78-6	Ester
J	n-Heptane	142-85-5	Saturated Hydrocarbon
K	Sodium Hydroxide, 40%	1310-73-2	Inorganic Base
L	Sulfuric Acid, 96%	7664-93-9	Inorganic Mineral Acid
M	Nitric acid 65%	7697-37-2	Inorganic mineral acid, oxidizing
N	Acetic acid 99%	64-19-7	Organic acid
O	Ammonia 25%	1336-21-6	Inorganic base
P	Hydrogen peroxide 30%	7722-84-1	Peroxide
S	Hydrofluoric acid 40%	7664-39-3	Inorganic mineral acid
T	Formaldehyde 37%	50-00-0	Aldehyde

STANDARD REMARKS

EN 374-5



EN 374-5



VIRUS

EN 374 Protective Gloves Against Chemical Substances And Microorganisms

This standard specifies the ability of gloves to protect the user from chemicals and microorganisms.

Marking Of Protective Gloves Against Microorganisms

For gloves that are protective against bacteria and fungi, the above-mentioned için biohazard pictogram mantar is applied. However, it is imperative that the glove be tested for leakage in accordance with EN374-2: 2013.

The biohazard pictogram for protection against bacteria, fungi and viruses is accompanied by the expression biyolojik VIRUS ına at the bottom. For this protective standard, it is essential that the glove is tested for bacteria and fungi in accordance with EN 374-2: 2013 and subjected to a bacteriophage penetration test in accordance with ISO 16604: 2004 (Method B).

EN 407
:2020



X1XXXX

EN 407 Protection Against Temperature Risks (Heat and / or Fire)

This standard covers the properties of heat and / or fire protection gloves, the methods of testing, the information and marking required to be provided.

For protective gloves against thermal risks, the performance levels in the main pictogram are given in the following order.

- a: Burning behavior (post-flame and after burning) (0-4)
- b: Contact heat (contact temperature & threshold temperature) (0-4)
- c: Convective heat (heat transfer index) (0-4)
- d: Radiant heat (heat transfer) (0-4)
- e: Small splashes of molten metal (0-4)
- f: Large quantities of molten metal (0-4)

NOTE: Using an X instead of a number means "the glove is not produced for the intended use."

PERFORMANCE LEVELS		1	2	3	4
a. Resistance to burning behavior	After flare time (s)	≤ 20s	≤ 10s	≤ 3s	≤ 2s
	After glow time (s)	-	≤ 120s	≤ 25s	≤ 5s
b. Contact heat resistance	Contact temperature (°C)	100°C	250°C	350°C	500°C
	Threshold time (s)	≥ 15s	≥ 15s	≥ 15s	≥ 15s
c. Convection heat resistance (s)		≥ 4s	≥ 7s	≥ 10s	≥ 18s
d. Radiant heat resistance (s)		≥ 7s	≥ 20s	≥ 50s	≥ 95s
e. Resistance to small splashes of molten metal (drops)		≥ 10	≥ 15	≥ 25	≥ 35
f. Resistance to large quantity of molten metals (mass)		30g	60g	120g	200g

STARLINE

USER'S GUIDE



Maintenance and Cleaning

We recommend you to clean gloves by a normal detergent with 40-60°C of water with maximum of 3 times. After the washing, the performance may not be seen which it is featured in associated pictograms. It is the responsibility of user to control whether glove is suitable for intended use or not, whether it is complete or not and whether protective functions are undamaged or not. User should carry out an examination against potential defects which are likely to adversely affect protection functions (punctures, tears, damaged seams, etc.).



Service Life

Gloves should be used within three years as of the manufacture date. Service life of the gloves are affected by several factors such as cold, hot, chemicals, sunlight and inadvisable storage.



Storage

Storage is a part of the maintenance and cleaning but is often ignored. Protective gloves should be stored in their original packaging which will keep them away from direct sunlight, chemicals and abrasive materials and protect them against physical damages of the hard surfaces or materials when it is not used or during shipment. Product should be stored in a dry and well-ventilated place. Availability of excessive humidity or intense light may adversely affect the product quality.

Order Information

MODEL	Size	Barcode	Box Quantity	Box Dimension	Box Weight
E-540	6.5	8680907971577	72 Pairs	42 x 32 x 42cm	12.20 kg.
E-540	7.5	8680907971584	72 Pairs	42 x 32 x 42cm	12.50kg.
E-540	8.5	8680907929240	72 Pairs	42 x 32 x 42cm	12.75kg.
E-540	9.5	8680907929257	72 Pairs	42 x 32 x 42cm	13.00kg.
E-540	10.5	8680907929264	72 Pairs	42 x 32 x 42cm	13.24kg.