

### STL-1004, STL-1005, STL-1006 SFT Nitrile Gloves

These gloves have powerful grip features to hold objects in dry and wet environments. Because of its nylon & spandex lining, the hands are allowed to breathe. The patented foam nitrile coating is ultra-thin. There are full and half-coated varieties available to meet the user's needs when considering applications where there is a lot of contact with the liquid.

#### Glove Coating

It is coated with nitrile material which prevents the penetration of liquids.



#### Marking Field

Includes all information required to be provided as per the European norms.



#### Extra Dots

The point is reinforced to provide better grip.

#### Elastic Wrist Strap

It is designed to keep gloves fitted and to prevent exterior substances from penetrating into the gloves.

#### Edge Color

Color separation has been made on the wristband part so that the size separation can be easily detected.

7/S 8/M 9/L 10/XL

### Technical Specifications

Lining Material	15-G Nylon + Spandex
Coating Material	<b>SFT</b> Foam Nitrile
Color	Gray / Black
Sizes	7/S, 8/M, 9/L, 10/XL
Units per Package	120 Pairs
Packaging	12 Pairs
Category	CAT II
Standards	EN 388:2016 (4131X) EN 407:2004 (X1XXXX) EN 420: 2003+A1:2009



SMART FOAM TECHNOLOGY



STL-1004



STL-1005



STL-1006

# STARLINE

## COATED AREA AND LINING MATERIAL

STL-1004



STL-1005



STL-1006



 Indicates coated parts.



### NITRILE COATING

**NBR**

These gloves protect the hands from liquid penetration through the full nitrile coating on the palm side and also provides protection against alkalies, oils, greases, animal fats and many other solvents.



### NYLON + SPANDEKS LINING

Seamless nylon and spandex lining provide excellent comfort during applications where objects are held and mounted. Provides protection against sweating through its excellent air permeability.

## STANDARDS

These gloves are intended to protect the hands against mechanical hazards as defined in the PPE Regulation (EU) 2016/425. This product is certified as per EN420 (General requirements and inspection methods for protective gloves), EN388 (Mechanical Risk Protection) and EN407 (Protective gloves against thermal risks).

EN 388:2016



4131X

EN 420:2003

+A1:2009



EN 407:2004



X1XXXX



Dexterity Level  
(min.1-max.5): 5

## Areas of Usage



Woodwork



Building and Construction



Glassware



Automotive and Transportation



Metal Production



Machine and Equipment



Logistics and Warehousing

These gloves are suitable for use in manufacturing of wood, wood products and cork products, manufacturing of paper and paper products, manufacturing of iron, steel and metal products, manufacturing of general purpose machines, manufacturing of planes or transport roads such as railways, automobiles, construction works in and outside of buildings, transportation and storage works, handling of glass and glass products and mechanical works.

## STANDARD REMARKS

### EN 388:2016



#### EN 388 Protective Gloves for Mechanical Risks

This standard covers features and test methods for protective gloves against mechanical risks such as abrasion, cutting, tearing, puncturing.

##### FEATURES:

Protective gloves conforming to this standard must meet all applicable properties of EN 420. The performance level of a protective glove against mechanical risks should be at a higher level for one of the attributes (wear, knife cutting, tearing, puncture and impact protection) that are classified according to the least features of each level shown in the table below.

Note - Gloves that meet the specifications for puncture resistance may not be suitable for protection against sharp-pointed objects such as hypodermic needles.

The letter **X** means that the test has not been done or can not be performed.

PERFORMANCE LEVELS	1	2	3	4	5
a - Abrasion resistance (number of cycles)	100	500	2000	8000	-
b - Cut resistance (index)	1,2	2,5	5,0	10,0	20,0
c - Tear resistance (N)	10	25	50	75	-
d - Puncture resistance (N)	20	60	100	150	-

PERFORMANCE LEVELS	A	B	C	D	E	F
e - Cut Resistance (N)	2	5	10	15	22	30
f - Protection Against Impact	Pass (P) / Failed (No sign)					

### EN 420



#### EN 420 General Specifications and Test Methods

This standard specifies the general requirements for the glove design and construction, protection against hazards, comfort, efficiency and marking and information applicable to all protective gloves. This standard also applies to arm protections.

Many gloves designed for electrical technicians or the most private applications such as surgical operations are governed by private and strict standards.

GLOVE SIZE	Fits Hand Size	Hand Circumference / Length	Minimum Glove Length
6	6	152/160 mm	220 mm
7	7	178/171 mm	230 mm
8	8	203/182 mm	240 mm
9	9	229/192 mm	250 mm
10	10	254/204 mm	260 mm
11	11	279/215 mm	270 mm

\* For more detailed information on Standards, you can obtain **EN European Glove Standards Guidelines** from [www.starlinesafety.com](http://www.starlinesafety.com).

## STANDARD REMARKS

### EN 407



abcdef

#### EN 407 Protection Against Temperature Risks (Heat and / or Fire)

This standard covers the properties of heat and / or fire protection gloves, the methods of testing, the information and marking required to be provided.

For protective gloves against thermal risks, the performance levels in the main pictogram are given in the following order.

- a:** Burning behavior (post-flame and after burning) (0-4)
- b:** Contact heat (contact temperature & threshold temperature) (0-4)
- c:** Convective heat (heat transfer index) (0-4)
- d:** Radiant heat (heat transfer) (0-4)
- e:** Small splashes of molten metal (0-4)
- f:** Large quantities of molten metal (0-4)

**NOTE:** Using an X instead of a number means "the glove is not produced for the intended use."

PERFORMANCE LEVELS		1	2	3	4
a. Resistance to burning behavior	After flare time (s)	≤ 20s	≤ 10s	≤ 3s	≤ 2s
	After glow time (s)	-	≤ 120s	≤ 25s	≤ 5s
b. Contact heat resistance	Contact temperature (°C)	100°C	250°C	350°C	500°C
	Threshold time (s)	≥ 15s	≥ 15s	≥ 15s	≥ 15s
c. Convection heat resistance (s)		≥ 4s	≥ 7s	≥ 10s	≥ 18s
d. Radiant heat resistance (s)		≥ 7s	≥ 20s	≥ 50s	≥ 95s
e. Resistance to small splashes of molten metal (drops)		≥ 10	≥ 15	≥ 25	≥ 35
f. Resistance to large quantity of molten metals (mass)		30g	60g	120g	200g

#### SMART FOAM TECHNOLOGY



#### STARLINE Smart Foam Technology

**SMARTFIT:** The SFT coating penetrates halfway into the liner. The skin only contacts the soft lining. The polymer does not touch the skin. This also leads to a high amount of lining removed from the compound and an increase in hand strength, allowing for high flexibility. This flexibility allows the PFT gloves

to follow the nose of your hands more naturally. This gives the user a perfect fit that provides perfect comfort.

**SMARTBREATH:** Thanks to the "micro-capillary channels", the heat generated in the glove is immediately released to keep the hand more comfortable. These air ducts are carefully placed in the coating of the SFT gloves. Air ducts extend from inside the coating to outside of the glove.

**SMARTDURABILITY:** Using Smartdurability technology, SFT coated gloves are made extremely durable. It is at least 30% more durable than the next best glove!

**SMARTGRIP:** The ability to grip gloves thanks to micro-capillary channels is excellent on all surfaces. We do 27 different tests to see the comprehension of all end-use applications. Objects: Metal, Glass, Wood Surfaces: Rough, Smooth, Wavy Medium: Dry, Wet, Oily Total 3x3x3 = 27 CROWN TEST

# STARLINE

## ● User Information

---



### **Maintenance and Cleaning**

We recommend you to clean gloves by a normal detergent with 40-60°C of water with maximum of 3 times. After the washing, the performance may not be seen which it is featured in associated pictograms. It is the responsibility of user to control whether glove is suitable for intended use or not, whether it is complete or not and whether protective functions are undamaged or not. User should carry out an examination against potential defects which are likely to adversely affect protection functions (punctures, tears, damaged seams, etc.).



### **Service Life**

Gloves should be used within three years as of the manufacture date. Service life of the gloves are affected by several factors such as cold, hot, chemicals, sunlight and inadvisable storage.



### **Storage**

Storage is a part of the maintenance and cleaning but is often ignored. Protective gloves should be stored in their original packaging which will keep them away from direct sunlight, chemicals and abrasive materials and protect them against physical damages of the hard surfaces or materials when it is not used or during shipment. Product should be stored in a dry and well-ventilated place. Availability of excessive humidity or intense light may adversely affect the product quality.

# STARLINE

## Order Information

MODEL	Size	Barcode	Box Quantity	Box Dimension	Box Weight
STL-1004	5 / XXS	8680907968768	120 Pairs	23 x 32 x 53cm	4.00kg.
STL-1004	6 / XS	8680907961745	120 Pairs	23 x 32 x 53cm	4.50kg.
STL-1004	7 / S	8680907945721	120 Pairs	23 x 32 x 53cm	5.00kg.
STL-1004	8 / M	8680907945738	120 Pairs	23 x 32 x 53cm	5.50kg.
STL-1004	9 / L	8680907945783	120 Pairs	23 x 32 x 53cm	6.00kg.
STL-1004	10 / XL	8680907945790	120 Pairs	23 x 32 x 53cm	6.50kg.
STL-1004	11 / XXL	8680907967587	120 Pairs	23 x 32 x 53cm	7.00kg.
STL-1004	12 / 3XL	8680907968751	120 Pairs	23 x 32 x 53cm	7.50kg.

MODEL	Size	Barcode	Box Quantity	Box Dimension	Box Weight
STL-1005	6 / XS	8680907961752	120 Pairs	23 x 32 x 53cm	6.00kg.
STL-1005	7 / S	8680907945806	120 Pairs	23 x 32 x 53cm	6.75kg.
STL-1005	8 / M	8680907945813	120 Pairs	23 x 32 x 53cm	7.25kg.
STL-1005	9 / L	8680907945820	120 Pairs	23 x 32 x 53cm	7.50kg.
STL-1005	10 / XL	8680907945844	120 Pairs	23 x 32 x 53cm	7.75kg.
STL-1005	11 / XXL	8680907967594	120 Pairs	23 x 32 x 53cm	8.00kg.

MODEL	Size	Barcode	Box Quantity	Box Dimension	Box Weight
STL-1006	6 / XS	8680907967303	120 Pairs	23 x 32 x 53cm	6.80kg.
STL-1006	7 / S	8680907945851	120 Pairs	23 x 32 x 53cm	7.25kg.
STL-1006	8 / M	8680907945868	120 Pairs	23 x 32 x 53cm	8.00kg.
STL-1006	9 / L	8680907945875	120 Pairs	23 x 32 x 53cm	8.50kg.
STL-1006	10 / XL	8680907945882	120 Pairs	23 x 32 x 53cm	9.00kg.
STL-1006	11 / XXL	8680907967617	120 Pairs	23 x 32 x 53cm	9.50kg.